

Reusche Colors Transparent Series

Profile:

High gloss, transparent

Firing Temperature:

1050-1080°F (566-582C) Firing cycles may vary based on kiln size, load size, substrate, etc.

Mixibility:


All colors within the range are fully intermixable,
Testing recommended.

Application:

Supplied as powder or pastes for screen printing, either hot or cold,
and for hand painting.

Health & Safety:

For detailed Health and Safety requirements consult the appropriate
Material Safety Data Sheets.



These colors contain lead and/or cadmium. Do not use on food bearing surfaces, toys or children's items.

Reusche Colors
Transparent Series
Recommended Firing Temperature 1050-1080F

| Product Number | Description | Color Swatch |
|-----------------------|--------------------|---|
| D24418 | Smoke Grey |  |
| D29400 | Transp. Brown |  |
| D22891 | Carmine 2777 |  |
| D22932 | Carmine |  |
| D211513 | Ruby |  |
| D21877 | Violet 2B151 |  |
| D221620 | Violet 2803 |  |
| D232255 | Yellow |  |
| D231176 | Amber L349 |  |
| D25822 | Chartreuse |  |
| D26169 | Green DO541 |  |
| D261676 | Green V554 |  |
| D26346 | Green |  |
| D26762 | Turquoise |  |
| D26354 | Turquoise Green |  |
| D27778 | Blue |  |
| D273359 | Blue |  |